








## YellowTop Specs

OPTIMA YELLOWTOP DUAL PURPOSE (STARTING & DEEP CYCLE) BATTERIES							
MODEL NUMBER	 D34/78	 D75/25	 D34	 D35	 D51 & D51R	 D27F	 DS46B24R
PERFORMANCE							
Voltage	12v	12v	12v	12v	12v	12v	12v
Cold Cranking Amps @ 0F	750	620	750	620	450	830	450
Cranking Amps @ 32F	870	770	870	770	575	1025	575
Reserve Capacity	120	100	120	100	66	140	66
Capacity (C/20 Rate)	55	48	55	48	38	66	38
Internal Resistance (ohms)	0.0028	0.003	0.0028	0.003	0.0046	0.0025	.0046
PHYSICAL SPECS							
Length	10"	9 5/16"	10"	9 5/16"	9 5/16"	12 3/16"	9 5/16"
Width	6 7/8"	6 13/16"	6 7/8"	6 13/16"	5 1/16"	6 13/16"	5 1/16"
Height	7 13/16"	7 5/8"	7 13/16"	7 5/8"	8 15/16"	8 3/4"	8 15/16"

Minimum Weight (lbs)	43.5	37.8	42.9	36.4	26	53.226	
Type Post/Terminal	Dual SAE & GM	Dual SAE & GM	SAE Post	SAE Post	SAE Post	SAE Post	SAE Post
BCI Group	34/78	75/25	34	35	51 & 51R	27F	S46B24R