







RedTop Specs

OPTIMA REDTOP STARTING BATTERIES						
MODEL NUMBER	 34 & 34R	 75/25	 34/78	 78	 25 & 35	 6V
PERFORMANCE						
Voltage	12v	12v	12v	12v	12v	6v
Cold Cranking Amps @ 0F	800	720	800	800	720	800
Cranking Amps @ 32F	1000	910	1000	1000	910	1000
Reserve Capacity	100	90	100	100	90	100
Capacity (C/20 Rate)	50	44	50	50	44	50
Internal Resistance (ohms)	0.003	0.003	0.003	0.003	0.003	0.0019
PHYSICAL SPECS						
Length	10"	9 5/16"	10"	10"	9 5/16"	10"
Width	6 7/8"	6 13/16"	6 7/8"	7 1/4"	6 13/16"	3 9/16"
Height	7 13/16"	7 5/8"	7 13/16"	7 3/16"	7 5/8"	8 1/8"

Minimum Weight (lbs)	37.9	33.1	38.8	39.5	31.7	18.4
Type Post/Terminal	SAE Post	Dual SAE & GM	Dual SAE & GM	Side Terminal	SAE Post	SAE Post
BCI Group	34 & 34R	75/35	34/78	78	25 & 35	N/A