




LITHIUM BLUE Battery

Discover® LITHIUM BLUE LiFePO₄ Premium Series batteries offer BMS controlled safety, long life, lightning fast charging performance and real-time Bluetooth access to battery State of Charge, voltage, current, temperature status. LITHIUM BLUE batteries reflect Discover's Design for Excellence philosophy, incorporating suitcase style carrying handles, terminal protection and field serviceable fuses. LITHIUM BLUE batteries are safe, easily to install and parallel for more capacity.



MECHANICAL SPECIFICATIONS

| Industry Reference | BCI: Low G24R DIN: | |
|------------------------|---------------------|-------|
| Length A (in/mm) | 10.3 | 262 |
| Width B (in/mm) | 6.9 | 175 |
| Height C (in/mm) | 8.3 | 210 |
| Total Height D (in/mm) | 8.3 | 210 |
| Weight (lbs/kgs) | 25.30 | 11.50 |
| Terminal * | M8 | |
| Cell(s) | Prismatic 4S1P | |
| Case Material | | |
| IP Rating | 67 | |
| Electrolyte | LiFePO ₄ | |

NOTE 1: Dimensions have a ±2 mm (0.08 in) tolerance. Weights may vary.
NOTE 2: Refer to [terminal guide](#) on website for torque values.

ELECTRICAL SPECIFICATIONS

| | |
|---|---------------------------------------|
| Open Circuit Voltage (V) | 12.8 |
| Charge Voltage (Bulk Vdc) | 13.8 - 14.2 |
| Max Absorption Voltage (U1 Vdc) | 13.8 |
| Float Voltage (U2 Vdc) | 13.6 |
| BMS Max. Voltage protection (Vdc) | 14.6 |
| Suggested Low Voltage Cutoff (Vdc) * | 12 |
| BMS Min. Voltage protection (Vdc) | 10.0 |
| Max. Continuous Charge Current (I Max. Adc) | 100 |
| Min. Finishing Charge Current (I Min. Adc) | 2%-3% C1 / Min. 200ma |
| Max Continuous Discharge Current (Adc) | 100 |
| Max Peak Current (Adc) | 250 |
| Self-Discharge (25°C / 77°F) | < 3% per month |
| Charge Temperature | Min: -18°C (-0°F) Max: 55°C (131°F) |
| Discharge Temperature | Min: -20°C (-4°F) Max: 60°C (140°F) |
| Storage Temperature | Min: -10°C (14°F) Max: 30°C (86°F) |

Electrical Specifications at 25°C.
* Do not exceed maximum voltage at the battery terminals.
CAUTION: Extra considerations must be given to depths of discharge, operating voltages and currents when designing systems for use at maximum operating temperatures.

PERFORMANCE SPECIFICATIONS

| Nominal Energy (kWh) | 1.28 | Minutes of Discharge | | | | |
|------------------------|------|----------------------|------|------|------|-------|
| | | @25A | @56A | @75A | @85A | @100A |
| Usable DoD | 100% | | | | | |
| Rated Wh Capacity (1C) | 1280 | 240 | 107 | 80 | 70 | 60 |
| Rated Ah Capacity (1C) | 100 | | | | | |

FEATURES

BLUETOOTH APP

- State of Charge
- Voltage / Current
- Temperature °F/°C

BUILT-IN SELF HEATING

HIGH-CURRENT BMS

- Field replaceable fuse protection

BENEFITS

ENHANCED RUNTIME

- Double the high-current runtime of lead-acid battery
- Up to 100% usable capacity
- Up to 100% Depth of Discharge

EXTENDED SERVICE LIFE

- 10x the life of lead-acid battery (BCI-06)
- Unlimited Partial State of Charge cycles
- Energy throughput warranty

FAST CHARGING

- Up to 5x faster than new lead-acid batteries
- Up to 10x faster than aged lead-acid batteries
- 2x faster than C/2 rated lithium batteries
- Opportunity charge at 1C rate anytime, regardless of SoC

SURGE POWER

- Surge power for inverter chargers
- Up to 3C peak power discharge rate
- Up to 1C continuous discharge rate

HIGH-EFFICIENCY

- Up to 50% more energy efficient than a lead-acid battery
- Up to 98% round-trip efficiency

PARALLEL POWER

- Easy to parallel more capacity
- Linear scaling of charge, discharge and peak capacity

QUICK INSTALL

- Fast installation. No special tools
- Drop-in lead-acid replacement

RELIABLE AND SAFE

- LiFePO₄ is safe
- Maintenance-free
- UL94 V0 flame retardant case and cover
- IP 67 rated

CERTIFIED QUALITY

Discover® manufacturing facilities are fully certified to ISO 9001/14001 and OSHA 18001 standards.


CERTIFICATION STANDARDS

- CE
- UN 38.3
- UL 2054


SHIPPING CLASSIFICATION

- UN 3480, Class 9 (Lithium batteries)


Fast Charging at .5C (2HR) to 1C (1HR)




Standard to Low Rate Charging at .2C (5HR) to .5C (2HR)




Voltage in Relation to Rate of Discharge




Discharge Voltage and Capacity vs. Temperature



Charge Performance (Lithium vs. Lead)



Discharge Performance (Lithium vs. Lead)



CAUTION: Direct connection to DC motors without proper safety protection, motor controllers, and external motor voltage clamping systems (such as high power anti-parallel diodes or braking resistor systems) may result in damage to the internal pack protection system which may result in unsafe situations. Please consult Discover technical support before directly connecting any motorloads.

Discover® reserves the right to make adjustments to this publication at any time, without notice or obligation. Data in this publication are for reference use only and models may vary from shown. It is the responsibility of the reader of this information to verify any and all information presented herein. For more information contact us at info@discoverbattery.com